



CX-1000

Gasdruckfeder Compact Xtreme




8

Grün
Blau
Rot
Gelb
Schwarz




Norm: VDI 3003
T: < 80 °C



$S = \text{Hub}$

S	L ± 0.25	L min	F1 [daN]	F2 [daN]	m [kg]	V [L]	Order No.
10	75	65	980	1330	0.36	0.030	CX-1000-10
15	85	70	980	1440	0.39	0.030	CX-1000-15
25	105	80	980	1610	0.43	0.040	CX-1000-25
38	135	97	980	1690	0.50	0.060	CX-1000-38
50	160	110	980	1770	0.56	0.070	CX-1000-50
63	205	142	980	1650	0.67	0.10	CX-1000-63
80	240	160	980	1730	0.75	0.12	CX-1000-80

EINBAUVARIANTEN



Druckmedium	N2
Max. Fülldruck (bei 20° C)	200 bar
Min. Fülldruck (bei 20° C)	25 bar
Betriebstemperatur	0° C - 80° C
Temperaturabhängige Druckerhöhung	0,3% / 1° C
Max. Kolbengeschwindigkeit	1,6 m/s
Empfohlene max Hübe / min (bei 20° C)	~ 70 - 200
Instandhaltungsset	3022836

D 3002B 03.2025