




TUS-3000


Gasdruckfeder High Speed



Grün
Blau
Rot
Gelb
Schwarz




T: < 80 °C

 $S = Hub$

S1	S	L ± 0.25	L min	F1 [daN]	F2 [daN]	m [kg]	V [L]	Order No.
25	25	170	145	3000	4200	6.35	0.20	TUS-3000-25
38	38.1	196.2	158.1	3000	4300	6.75	0.26	TUS-3000-38
50	50	220	170	3000	4400	7.50	0.32	TUS-3000-50
64	63.5	247	183.5	3000	4500	7.70	0.38	TUS-3000-64
80	80	280	200	3000	4600	8.10	0.46	TUS-3000-80
100	100	320	220	3000	4700	8.85	0.56	TUS-3000-100
125	125	370	245	3000	4700	9.90	0.69	TUS-3000-125
160	160	440	280	3000	4700	10.80	0.87	TUS-3000-160
200	200	520	320	3000	4800	12.20	1.07	TUS-3000-200
250	250	620	370	3000	4800	13.70	1.32	TUS-3000-250
300	300	720	420	3000	4800	15.30	1.57	TUS-3000-300

EINBAUVARIANTEN



Druckmedium	N2
Max. Fülldruck (bei 20° C)	150 bar
Min. Fülldruck (bei 20° C)	25 bar
Betriebstemperatur	0° C - 80° C
Temperaturabhängige Druckerhöhung	0,3% / 1° C
Max. Kolbengeschwindigkeit	2,0 m/s
Empfohlene max Hübe / min (bei 20° C)	~ 15 - 40
Instandhaltungsset	3019279